

Arvedi Tubi Acciaio S.p.A.

26100 Cremona - Italia
Via Acquaviva, 3 - Zona Porto Canale
Tel. +39 0372 4091
Fax +39 0372 413170

<http://www.arvedi.it/>

Cap.Soc. 4.000.000 EUR i.v.
Società interamente controllata
da Finarvedi S.p.A.
R.I. CR 00113630198
R.E.A. CR 90188
Mecc. Est. CR 000296
C.F. e Part. IVA IT 00113630198



DECLARATION OF PERFORMANCE

n. 10210-01072013-2

1. Unique product-type identification code:

profile	external dimensions	thicknesses	Steel grades:
circular section	ø 19 ÷ 355,6 mm	from 1,2 ÷ 16 mm	S235JRH – S275J0H – S275J2H – S355J0H – S355J2H – S355K2H – S275NH – S355NH – S420NH – S460NH – S275NLH – S355NLH – S420NLH – S460NLH
square section	90x90 ÷ 300x300 mm	from 3 ÷ 16 mm	
rectangular section	100x80 ÷ 400x200 mm	from 3 ÷ 16 mm	

- 2. Expected use: *Hot-rolled tubes for structural applications*
- 3. Manufacturer: *Arvedi Tubi Acciaio Spa, via Acquaviva, 3 – 26100 CR - Italy*
- 4. Mandatory: *Not applicable*
- 5. AVCP system: *system 2+*
- 6. Harmonized standard: *EN 10210-1:2006 – EN 10210-2:2006*
Notified body: *Istituto Italiano di Garanzia della Qualità, 1608 CPR P063*

7. Declared performance:

	Circular section	Square / rectangular section	Harmonized technical specification
Essential Feature	Performance		EN 10210-2
External dimensions	+/-1% with min: +/-0.5mm		
Thickness	-10% (+ Limited by weight tolerance)		
Ovality	2%		
Concavity / convexity	+/- 1.0%		
Angle between sides	90° +/-1°		
Radius	R ≤3.0 x T		
Twist	2 mm + 0.5 mm/m		
Straightness	2.0 mm / mt on the total length and ≤ 3mm on 1 single meter		
Mass	+/- 6% (On the single tube)		

Steel	Essential Features								Harmonized technical specification		
	Elongation	Yield load	Breaking load T<=3	Breaking load T>3	Resilience KV (10 mm)					Weldability (CEV)	Durability
					-50°C	-20°C	0°C	+20°C			
	%	MPa	MPa	MPa	J				%		
	Declared Performance										
S235JRH	26	235	360-510	360-510				27	0,37	If required, galvanized material	EN 10210-1
S275J0H	23	275	430-580	410-560			27		0,41		
S275J2H	23	275	430-580	410-560			27		0,41		
S355J0H	22	355	510-680	470-630			27		0,45		
S355J2H	22	355	510-680	470-630			27		0,45		
S355K2H	22	355	510-680	470-630		40			0,45		
S275NH	24	275	370-500			40			0,40		
S355NH	22	355	470-630			40			0,43		
S420NH	19	420	520-680			40			0,50		
S460NH	17	460	540-720			40			0,53		
S275NLH	24	275	370-500		27				0,40		
S355NLH	22	355	470-630		27				0,43		
S420NLH	19	420	520-680		27				0,50		
S460NLH	17	460	540-720		27				0,53		



Arvedi Tubi Acciaio S.p.A.

26100 Cremona - Italia
Via Acquaviva, 3 - Zona Porto Canale
Tel. +39 0372 4091
Fax +39 0372 413170

<http://www.arvedi.it/>

Cap.Soc. 4.000.000 EUR i.v.
Società interamente controllata
da Finarvedi S.p.A.
R.I. CR 00113630198
R.E.A. CR 90188
Mecc. Est. CR 000296
C.F. e Part. IVA IT 00113630198

Arvedi Tubi Acciaio 

The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Cremona, 09/06/2017

Noris Battocletti

Quality Manager


